DXI35DT/DXI55DT/DXI75DT/DXI95DT

WATER HEATING

DELUX INLINE

Instantaneous Hot Water





The Delux instantaneous water heaters are ideal for use where space is a premium and hot water is needed for hand washing in commercial applications such as, offices, shops, factories, schools/universities, hospitals, modular buildings. The unit includes an digital temperature display with accurate touch control.

DXI75D1


The temperature rise from ambient is affected by the water flow rate (faster = cooler). It is recommended that a flow restriction / spray head tap nozzle is used to attain the required performance and temperature. 3.5kW <2lpm, 5kW <3lpm max flow, 7.5kW <4lpm max flow & 9.5kW <6lpm max flow

As water temperatures vary dependent on time of year, winter may result in incoming temperatures 10°C or below and summer water temperatures can be upwards of 15°C. This needs to be taken into account when checking delivered temperature. As an example, the unit could deliver 49°C water in the summer (incoming water at 15°C) v's 44°C in winter (incoming water at 10°C) based on a flow rate of 1.5 litres per minute. Please note, this temperature could be lower if the incoming water supply is less than 10°C.

- Instant hot water for hand washing
- 3.5kW (DXI35DT), 5.5kW (DXI55DT), 7.5kW (DXI75DT) & 9.5kW (DXI95DT) models available
- Adjust outbound flow to control performance/ temperature
- High efficiency cast aluminium heating element
- Compact, stylish design

DXI35DT/DXI55DT

- Digital temperature display
- Accurate digital temperature control
- 1/2" inlet / outlet connections
- Recommended for use with spray head taps to attain desired water temperature
- Cable pre-wired





to ERP Energy ratings: A

